



48



(STANDARD TUBULAR)			
SIGN LENGTH	SIGN DEPTH SEE NOTE 6	UNITS REQUIRED SEE NOTE 5	
14'-0" OR LESS	4'-2" TO 5'-0"	9	
15'-0" TO 20'-0"	4'-2" TO 5'-0"	13	
21'-0" TO 24'-0"	4'-2" TO 5'-0"	17	
14'-0" OR LESS	5'-10" TO 10'-0"	17	
15'-0" TO 20'-0"	5'-10" TO 10'-0"	25	
21'-0" TO 24'-0"	5'-10" TO 10'-0"	33	



## NOTES:

- 1. Refer to applicable Standard Plan for additional mounting details.
- 2. Beveled washer for tapered flange only.
- 3. Elevator head bolt, hexagon nut, and lock washer shall be %6" diameter (18-8) stainless steel.
- 4. Furnish retroflective stick-ons for bolt head in same color as sign. Apply during installation.
- 5. One unit of A-2 hardware shall consist of one each; bolt nut, lock washer and beveled washer. Quantity listed includes 1 spare unit.
- Signs 9'-2" and 10'-0" in depth may be fabricated in three panel sections to avoid legend from being placed on a horizontal seam. Increase number of units of mounting hardware accordingly.

2½"

SEE NOTE 2

MOUNTING HARDWARE

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

TYPE A-2 MOUNTING HARDWARE FOR OVERHEAD LAMINATED TYPE A PANEL (BRIDGE MOUNTED AND TUBULAR SIGN STRUCTURES)

NO SCALE

**S88**